

01-11-00

A

Case Docket No. FUJR 16.835
 Filed by Express Mail
 (Receipt No. EL522353989US)
 on January 10, 2000
 pursuant to 37 CFR 1.10
 by Leonard Cooper

01/10/00
 Jc583 U.S. PTO

THE COMMISSIONER OF PATENTS AND TRADEMARKS
 Washington D.C. 20231
 Box Patent Applications

S I R:
 Transmitted herewith for filing is: ☒ a new application
☐ a c-i-p application of S.N. _____ filed _____

Inventor(s): Shinichi KURANAI; Fumiharu ETOH; Tomoyuki FURUTONO; Hiroki HAMACHI

For: NETWORK INTERCONNECTION APPARATUS AND METHOD

Enclosed are:

- ☒ 15 sheets of drawings.(Figs. 1-15)
- ☒ Specification, including claims and abstract (36 pages)
- ☒ Declaration
- ☒ An assignment of the Invention to FUJITSU LIMITED
- ☒ A certified copy of Japanese Application No. 11-153276
- ☒ An associate power of attorney
- ☐ A verified statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27
- ☒ Post card
- ☒ Recording fee (as indicated below)
- ☒ Information Disclosure Statement, PTO-1449, copies of 2 references
- ☐ Other _____
- ☐ Other _____

Jc511 U.S. PTO
 09/480735
 01/10/00

	Col. 1	Col. 2
FOR:	NO. FILED	NO. EXTRA
BASIC FEE		
TOTAL CLAIMS	8-20 =	0
INDEP CLAIMS	2-3 =	0
<input type="checkbox"/> MULTIPLE DEPENDENT CLAIMS PRESENTED		

*If the difference in Col. 1 is less than zero, enter "0" in Col. 2

SMALL ENTITY	
RATE	FEE
	\$345
x 9 =	\$
x 39 =	\$
x 130 =	\$
TOTAL	\$

OTHER THAN A SMALL ENTITY	
RATE	FEE
	\$690
x 18 =	\$
x 78 =	\$
x 260 =	\$
TOTAL	\$690

☐ Please charge our Deposit Account No. 08-1634 the amount of _____ to cover the filing fee and recording fee (if any)

☒ A check in the amount of \$730.00 to cover the filing fee and the recording fee (if any) is enclosed.

☒ The Commissioner is hereby authorized to charge payment of any fee associated with this communication or credit overpayment to Deposit Account No. 08-1634. A duplicate copy of this sheet is enclosed.

Helfgott & Karas, P.C.
 60th Floor
 Empire State Building
 New York, New York 10118-6098
 (212)643-5000

Respectfully Submitted,

[Signature]

Date: January 10, 2000

Any fee due with this paper, not fully covered by an enclosed check, may be charged on Deposit Acct No. 08-1634

- ☐ Aaron B. Karas, Reg. No. 18,923
- ☒ Samson Helfgott, Reg. No. 23,072
- ☐ Leonard Cooper, Reg. No. 27, 625
- ☐ Linda S. Chan, Reg. No. 42,400
- ☐ Jacqueline M. Steady, Reg. No. 44,354
- ☐ Harris A. Wolin, Reg. No. 39,432

09480735-011000

NETWORK INTERCONNECTION APPARATUS AND METHOD

BACKGROUND OF THE INVENTION

(1) Field of the Invention

5 The present invention relates to network interconnection apparatus and method, and more particularly, to an apparatus and method for interconnecting a LAN (Local Area Network) and an ATM (Asynchronous Transfer Mode) network to perform communications.

10 (2) Description of the Related Art

 ATM is a connection type communication mode developed so as to permit, within a single network, communications of multimedia information including data, voice, moving images, etc. to be performed at respective
15 required rates while ensuring respective required qualities.

 With conventional LANs which are preconditioned on broadcast function and connectionless type communication mode, it is difficult to ensure communication band or quality with respect to the requirements of such real-time
20 communications of voice, moving images, etc. Attempts have therefore been made to construct LAN-ATM in which ATM is applied to LAN, and there is a need for economical and seamless connection between the two.

 To permit interconnection of LAN and ATM, ATM
25 Forum LAN Emulation (hereinafter abbreviated as LANE) Ver. 1.0, for example, is prescribed. LANE is a set of specifications that permit the connection and communications

between an existing LAN environment and an ATM network environment, and emulation is carried out using the MAC (Media Access Control) layer of the LAN. Specifically, nodes are interconnected permanently by SVC (Switched Virtual Connection) at best-effort UBR (Unspecified Bit Rate) of the ATM network, to exchange data frames between the LAN and the ATM. Interconnection of LAN and ATM is also prescribed in LANE Ver. 2.0 and MPOA (Multi Protocol Over ATM) Ver. 1.0.

10 Meanwhile, with the advent of a multimedia network era, increasing attention has recently come to be directed to the QoS (Quality of Service) which networks provide. What is demanded from networks is, for example, up to at what degree of resolution and at what rate of transmission
15 video can be sent to a destination.

 Conventional techniques for guaranteeing QoS include a technique disclosed in Japanese Patent Application Laid-open Publication No. 9-331360, for example, in which call connection is tried first according to set QoS
20 parameters, and if the call connection fails, the call connection request is repeatedly tried with the QoS request level gradually lowered until the call connection succeeds, to thereby guarantee QoS.

 Concerning the guarantee of QoS, which is an
25 advantage of ATM, LANE Versions 1.0 and 2.0 and MPOA Ver. 1.0 mentioned above have a problem in that they are not designed to guarantee QoS.

In LANE Ver. 1.0, for example, although ATM network is used to transfer LAN data through UBR connection, QoS is not guaranteed.

In the conventional technique disclosed in Japanese Patent Application Laid-open Publication No. 9-331360, on the other hand, QoS corresponding to physical port, destination address, application identifier, etc. is set beforehand, and accordingly, a problem arises in that the QoS guaranteed does not necessarily reflect actual traffic.

In addition, since the call connection request is repeated with the QoS level lowered until call is established, without regard to the status of network resources, there is a possibility of a large number of lost calls being generated, giving rise to a problem that useless traffic occurs in the network.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a network interconnection apparatus which is capable of efficiently guaranteeing an optimum QoS suited to the status of actual traffic and network, thereby permitting high-performance network interconnection without entailing lost calls.

Another object of the present invention is to provide a network interconnection method which is capable of efficiently guaranteeing an optimum QoS suited to the status

of actual traffic and network, thereby permitting high-performance network interconnection without entailing lost calls.

To achieve the first object, there is provided a
5 network interconnection apparatus for interconnecting a LAN
and an ATM network to perform communications. The network
interconnection apparatus comprises routing information
managing means for managing routing information of the ATM
network, statistical information managing means for managing
10 statistical information on traffic of the LAN, QoS setting
means for setting QoS which the ATM network ought to
guarantee, based on the statistical information, QoS
guarantee determining means for determining based on the
routing information whether or not the set QoS can be
15 guaranteed, QoS adjusting means for adjusting the QoS so
that the QoS can be guaranteed, if it is judged that the QoS
cannot be guaranteed, and call connection control means for
performing call connection according to the QoS which can be
guaranteed.

20 There is also provided a network interconnection
method for interconnecting a LAN and an ATM network to
perform communications. The network interconnection method
comprises managing routing information of the ATM network,
managing statistical information on traffic of the LAN,
25 setting QoS which the ATM network ought to guarantee, based
on the statistical information, determining based on the
routing information whether or not the set QoS can be

09480735 014000
000110 5208460

guaranteed, adjusting the QoS so that the QoS can be guaranteed, if it is judged that the QoS cannot be guaranteed, and performing call connection according to the QoS which can be guaranteed.

5 The above and other objects, features and advantages of the present invention will become apparent from the following description when taken in conjunction with the accompanying drawings which illustrate preferred embodiments of the present invention by way of example.

10 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram illustrating the principle of a network interconnection apparatus according to the present invention;

15 FIG. 2 is a diagram showing in detail the configuration of the network interconnection apparatus;

FIG. 3 is a diagram showing a network configuration to which the network interconnection apparatus is applied;

20 FIG. 4 is a diagram illustrating LANE;

FIG. 5 is a diagram illustrating statistical information;

FIG. 6 is a diagram showing information elements of a call connection request message;

25 FIG. 7 is a diagram showing QoS parameters;

FIG. 8 is a diagram showing results of QoS settings;

FIG. 9 is a diagram illustrating inter-node routing information;

FIG. 10 is a diagram showing a designated transit list table for routing from node A to node E;

5 FIG. 11 is a diagram showing contents of settings of the information elements of a call connection request message;

FIG. 12 is a diagram also showing contents of settings of the information elements of a call connection request message;

FIG. 13 is a diagram illustrating QoS information;

FIG. 14 is a sequence diagram illustrating a route selection procedure; and

FIG. 15 is a chart illustrating a procedure of a network interconnection method.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will be hereinafter described with reference to the drawings. FIG. 1 illustrates the principle of a network interconnection apparatus according to the present invention. A network interconnection apparatus 10 provides interconnection (hereinafter referred to as interworking) between a LAN and an ATM network for communications therebetween while guaranteeing optimum QoS.

In the illustrated network configuration, a LAN 1a and an ATM network 2 are interconnected by a node A, and the

ATM network 2 and a LAN 1b are interconnected by a node E. Also, as shown in the figure, the LANs 1a and 1b each include a plurality of information terminal units connected to their circuit having bus-type topology, for example.

5 Where a call connection is to be established along the route of LAN 1a → ATM network 2 → LAN 1b, the network interconnection apparatus 10 of the present invention is arranged at the node A.

10 Routing information managing means 11 collects and manages routing information of PNNI (Private Network-Network Interface) which reflects current resource status (hereinafter referred to as actual network) of the ATM network 2. PNNI has the function of both routing and signaling between ATM switches and is a protocol prescribing
15 the interface between ATM switches.

 The routing information includes, for example, ACR (available cell rate), CTD (cell transfer delay), CDV (cell delay variation), etc. between nodes.

 Statistical information managing means 12 manages
20 statistical information which reflects current traffic status (hereinafter referred to as actual traffic) of the LAN. The statistical information is numerical information which has been processed and modified to a high degree according to purposes, and includes, for example, a traffic
25 volume which is the sum of frame sizes (frame lengths) or the total number of frames within a fixed time interval (per unit time), an average traffic volume thereof, etc.

QoS setting means 13 sets QoS which the ATM network 2 ought to guarantee, in accordance with the statistical information. As the QoS are specified types (parameters) including, for example, service category, band, delay, fluctuation, etc.

QoS guarantee determining means 14a determines based on the routing information whether or not the QoS set by the QoS setting means 13 can be guaranteed.

If it is judged that the QoS cannot be guaranteed, QoS adjusting means 14b adjusts the QoS so that the QoS can be guaranteed.

Call connection control means 15 establishes connection of an SVC (Switched Virtual Connection) call according to the QoS which the QoS guarantee determining means 14a has judged to be able to be guaranteed. In FIG. 1, call is connected via a route i of node A → node B → node E, thus establishing a path guaranteeing the QoS.

Specifically, QoS parameters as determined are specified in a call connection request message. Where a call is originated at the node A and terminated at the node E via the node B, a path guaranteeing QoS is set up at the time when the connection between the nodes is established.

As described above, the network interconnection apparatus 10 according to the present invention determines QoS which can be guaranteed, based on the routing information of the ATM network and the statistical information of the LAN to connect call.

09460733 041000
This makes it possible to set optimum QoS suited to the status of actual traffic and actual network, and since call connection control is performed after the optimum QoS is determined, it may be performed only once, whereby
5 interwork control can be carried out efficiently without entailing useless lost calls.

The configuration of the network interconnection apparatus 10 according to the present invention will be now described in detail. FIG. 2 shows details of the
10 configuration of the network interconnection apparatus 10. In the following, description of those elements which are already explained with reference to FIG. 1 will be omitted.

LAN circuit control means 16 incorporates therein a LAN circuit interface. ATM circuit control means 17
15 incorporates therein an ATM network circuit interface.

Interwork QoS guaranteeing means 14 includes the QoS guarantee determining means 14a and the QoS adjusting means 14b.

QoS information notifying means 18 provides QoS
20 information to an external maintenance terminal unit 20 connected to the network interconnection apparatus 10. The QoS information is information specifying, for example, parameters of the guaranteed QoS, or parameters of the QoS which cannot be guaranteed and the reason for the failure to
25 guarantee the QoS, etc. The maintenance terminal unit 20 performs maintenance, management and monitoring of the network interconnection apparatus 10.

If there exist a plurality of route options with respect to the requested QoS when call is to be connected, route selecting means 19 selects a route according to preferential QoS, as described in detail later.

5 The operation of the apparatus will be now described. In FIG. 2, the arrow-headed dashed lines indicate the flow of information data, and the arrow-headed solid lines indicate the flow of control signals.

[S1] The statistical information managing means 12
10 generates statistical information based on actual traffic information received via the LAN circuit control means 16 and manages the generated information.

[S2] The routing information managing means 11
15 manages routing information which is actual network information received via the ATM circuit control means 17.

[S3] The QoS setting means 13 sets QoS in accordance with the statistical information, and requests the set QoS with respect to the interwork QoS guaranteeing means 14.

20 [S4] The interwork QoS guaranteeing means 14 requests the routing information managing means 11 to provide routing information.

[S5] The routing information managing means 11
25 sends in reply the routing information to the interwork QoS guaranteeing means 14.

[S6] Based on the routing information received from the routing information managing means 11, the

interwork QoS guaranteeing means 14 determines whether or not the requested QoS can be guaranteed. If the requested QoS can be guaranteed, the flow proceeds to Step S7, and if not, the flow proceeds to Step S9. If it is judged that
5 there are a plurality of routes guaranteeing the requested QoS, the flow proceeds to Step S10.

[S7] The interwork QoS guaranteeing means 14 sends a call connection instruction to the call connection control means 15.

10 [S8] The call connection control means 15 performs call connection control according to the QoS which has been judged to be able to be guaranteed, whereupon the flow proceeds to Step S14.

[S9] The interwork QoS guaranteeing means 14
15 lowers the QoS level for adjustment, and the flow returns to Step S4.

[S10] The interwork QoS guaranteeing means 14 sends route option information including the QoS and the route options to the route selecting means 19.

20 [S11] The route selecting means 19 transmits the route option information to the maintenance terminal unit 20.

[S12] The user specifies the QoS to which he or she desires to give priority, and transmits the specified QoS through the maintenance terminal unit 20 to the route
25 selecting means 19.

[S13] The route selecting means 19 selects a route in accordance with the preferential QoS specified by the

user, and sends information on the selected route to the interwork QoS guaranteeing means 14, whereupon the flow returns to Step S4.

[S14] The QoS information notifying means 18
5 notifies the maintenance terminal unit 20 of the QoS information received from the interwork QoS guaranteeing means 14.

Taking LANE as an example of LAN-ATM interworking, a first embodiment of the present invention will be now
10 described in detail wherein the embodiment is applied to the decision of QoS at the time of establishment of Data Direct VCC (hereinafter referred to as ATM connection) in LANE.

The QoS for ATM connection is in actuality specified by specifying or combining information elements in
15 a call connection request message (SETUP message), and accordingly, the method of setting the QoS will also be explained.

FIG. 3 shows a network configuration to which the network interconnection apparatus 10 is applied. A LAN 1a
20 and an ATM network 2 are interconnected by a node A, and the ATM network 2 and a LAN 1b are interconnected by a node E.

The nodes A through E are each an ATM switched node, and the nodes A and E have a built-in function equivalent to LEC (LAN Emulation Client) in LANE for the
25 LAN-ATM interworking.

LEC is a client function in LAN emulation whereby an existing LAN is virtually realized in ATM network.

000110"SE203450

The individual nodes are connected to one another by means of PNNI protocol and constitute the ATM network 2. The LANs 1a and 1b each include a plurality of LAN units (information terminal units) connected to their circuit 5 having bus-type topology.

Where call connection (ATM connection) from the node A to the node E is to be established to permit communications between the LAN units A1 and E1, the network interconnection apparatus 10 of the present invention is 10 arranged at the node A. The maintenance terminal unit 20 is connected to the network interconnection apparatus 10.

FIG. 4 is a diagram illustrating LANE. A LEC 1, to which the LAN unit A1 is connected, is included in the node A shown in FIG. 3, and a LEC 4, to which the LAN unit 15 E1 is connected, is included in the node E also shown in FIG. 3. A LES (LAN Emulation Server) and a BUS (Broadcast and Unknown Server) are included in the ATM network 2.

LES is an address resolution server function in LAN emulation whereby an existing LAN is virtually realized 20 in ATM network.

BUS is a function of achieving LAN broadcasting in LAN emulation whereby an existing LAN is virtually realized in ATM network.

It is here assumed that TCP/IP data frames 25 (hereinafter simply referred to as frames) are transferred from the LAN unit A1 to the LAN unit E1. In this case, it is necessary that the LEC 1 be informed of the ATM address

of the LEC 4 when ATM connection is to be established between the LECs 1 and 4.

[S20] The LEC 1 queries the LES about the ATM address of the LEC 4.

5 [S21] While waiting for a response from the LES, the LEC 1 transfers frames to the BUS.

[S22] The BUS broadcasts the frames received from the LEC 1 to the LECs 2 to 4. Since the frames are thus broadcast via the BUS, they can be transmitted to the LEC 4
10 even though there is no direct ATM connection established between the LECs 1 and 4. The other LECs than the LEC 4, that is, the LECs 2 and 3, discard the received frames.

[S23] The LEC 1 receives the ATM address of the LEC 4 from the LES.

15 [S24] The LEC 1 transmits a call connection request message to the LEC 4 and establishes ATM connection. Then, the LEC 1 switches the frame transmission from the transmission via the BUS to the transmission through the ATM connection, to transfer frames directly to the LEC 4.

20 Let us now consider, as the first embodiment, the case where frames are transmitted from the LAN unit A1 connected to the LAN 1a, with which the node A interworks, to the LAN unit E1 connected to the LAN 1b, with which the node E interworks.

25 Frames to be transmitted from the LAN unit A1 to the LAN unit E1 are first sent from the LAN circuit control means 16 to the ATM circuit control means 17, both shown in

FIG. 2. To establish ATM connection with respect to the node E accommodating the LAN unit E1 which is the destination of the frames, the node A queries the LES about the ATM address of the node E, following the procedure
5 prescribed by LANE explained above with reference to FIG. 4.

Transfer of the frames via the BUS is continued until the ATM address of the terminating node E is resolved. Specifically, the ATM circuit control means 17 of the node A sets up TCP/IP connection to the node E via the BUS, and
10 transfers the frames over the TCP/IP connection until the ATM address is resolved.

While the transfer is under way, the statistical information managing means 12 measures, through the LAN circuit control means 16, frame sizes or the number of
15 frames transmitted per unit time over the TCP/IP connection, as information indicative of a traffic characteristic, and manages the acquired information as the statistical information.

FIG. 5 illustrates the statistical information.
20 The statistical information managing means 12 generates statistical information as actual traffic information, based on the information obtained via the LAN circuit control means 16, and manages the generated information in the form of a statistical information management table 11a.

25 In the illustrated statistical information management table 11a are described traffic volumes per unit time sampled (in the illustrated example, sampled five

times) with respect to each TCP/IP connection, and an average traffic volume thereof.

For example, in the case of the TCP/IP connection identifier #1, the traffic volumes sampled five times are
5 all "19.2 kbps", and accordingly, "19.2 kbps" is described as the average traffic volume.

When the ATM address of the terminating node E has been resolved, it is necessary that the node A transmit a call connection request message to the node E to establish
10 ATM connection with respect thereto.

FIG. 6 shows information elements of such a call connection request message. The call connection control means 15 transmits a call connection request message to the node E via the ATM circuit control means 17. When a
15 response message is thereafter received from the node E, ATM connection is established between the nodes A and E.

The call connection request message includes ATM Traffic Descriptor, Broadband Bearer Capability, DTL, Called Party Number, etc., as general information elements 15a
20 specifying QoS.

The ATM Traffic Descriptor specifies, as its contents, PCR (Peak Cell Rate), SCR (Sustainable Cell Rate), MBS (Maximum Burst Size), etc.

The Broadband Bearer Capability specifies as its
25 contents service category, mentioned later, etc., and the DTL specifies as its contents a list of routing (list of transit nodes) up to the terminating node, etc. The Called

Party Number specifies as its contents the ATM address of the terminating node, etc.

According to the present invention, the above information elements are determined in accordance with the actual traffic and the actual network, in order to set up ATM connection which can guarantee optimum QoS.

FIG. 7 shows QoS parameters. QoS parameters 13-1, which are set by the QoS setting means 13 and are requested with respect to the interwork QoS guaranteeing means 14, include service category, band, delay, and fluctuation.

As the service category is specified CBR (Constant Bit Rate) or VBR (Variable Bit Rate).

As the band, PCR (Peak Cell Rate), SCR (Sustainable Cell Rate), and MBS (Maximum Burst Size) are specified. CTD (Cell Transfer Delay) is specified as the delay, and CDV (Cell Delay Variation) as the fluctuation.

Where CBR is set as the service category, PCR alone is specified as requested band specification information in the information element for the ATM Traffic Descriptor in the call connection request message. In the case where VBR is set as the service category, it is necessary that PCR, SCR and MBS be specified as the requested band specification information.

In determining the service category, CBR is selected if [average traffic volume \times 1.2 > maximum traffic volume] and VBR is selected if [average traffic volume \times 1.2 \leq maximum traffic volume].

09430735 011000
This determination is in accord with a method wherein CBR is judged to be the applicable service category if the maximum traffic volume among the sampled traffic volumes is not greater than the average traffic volume plus
5 20%, and VBR is judged to be the applicable service category if the maximum traffic volume is greater than the average traffic volume plus 20%. MBS can be obtained by converting the traffic volume at the time of burst into the number of ATM cells.

10 In general, CBR is considered to be sensitive to delay while VBR is considered to be sensitive to fluctuation; therefore, when determining CTD and CDV, a small CTD value (small delay), for example, 20 μ s or less, is required to be set if the service category is CBR.

15 If the service category is VBR, a small CDV value (small fluctuation), for example, 4 μ s or less, is required to be set.

Accordingly, in the case where the statistical information is the one shown in FIG. 5 as the TCP/IP
20 connection identifier #1 (where frames are being transmitted using the TCP/IP connection with the identifier #1), the QoS setting means 13 may set QoS as follows: service category = CBR, requested band specification information PCR = 50 cps (= 19.2 kbps), CTD = 20 μ s or less, and CDV = arbitrary.

25 Where the statistical information is the one also shown in FIG. 5 as the TCP/IP connection identifier #2, QoS can be set as follows: service category = CBR, requested

band specification information PCR = 12500 cps (= 4.8 Mbps),
CTD = 20 μ s, and CDV = arbitrary.

Further, where the statistical information is the
one shown in FIG. 5 as the TCP/IP connection identifier #3,
5 QoS can be set as follows: service category = VBR, requested
band specification information PCR = 15000 cps (= 5.76 Mbps),
SCR = 6250 cps (= 2.4 Mbps), MBS = 30000 cells (= 15000 +
15000 cells at the time of burst; i.e., the sum of the value
obtained by converting the third sampled volume "5.76 Mbps"
10 into the number of ATM cells and the value obtained by
converting the fourth sampled volume "5.76 Mbps" into the
number of ATM cells), CTD = arbitrary, and CDV = 4 μ s or
less.

FIG. 8 collectively shows the results of the above
15 QoS settings. In the figure are shown the results of the
QoS settings (hereinafter referred to as QoS parameter
setting information) corresponding to the TCP/IP connection
identifiers #1 to #3, respectively.

In the following description of the first
20 embodiment, it is assumed that QoS parameter setting
information 13a associated with the TCP/IP connection
identifier #1 has been set by the QoS setting means 13.

The QoS setting means 13 notifies the interwork
QoS guaranteeing means 14 of the QoS parameter setting
25 information 13a and the ATM address of the terminating node
E. On receiving the QoS parameter setting information 13a
and the ATM address of the terminating node E from the QoS

setting means 13, the interwork QoS guaranteeing means 14 requests the routing information managing means 11 to provide routing information on routing up to the terminating node E.

5 FIG. 9 illustrates inter-node routing information. A route of node A → node B → node E constitutes a route i, a route of node A → node C → node E constitutes a route ii, and a route of node A → node D → node E constitutes a route iii. As routing information of PNNI between
10 respective nodes, the values of ACR, CTD and CDV are set as shown in the figure.

FIG. 10 shows a designated transit list table for routing from the node A to the node E. On receiving the inter-node routing information as shown in FIG. 9 via the
15 ATM circuit control means 17, the routing information managing means 11 updates topology data base (TDB) under management, and when requested to provide routing information on routing from the originating node to the terminating node, it creates a designated transit list (DTL)
20 table 12a.

In the DTL table 12a, node A → node B → node E is specified as the routing list for the route i. In ACR 12a-1 is described the available cell rate. In the case of the route i, ACR in the direction of node A → node B is 1000
25 cps (cells per second) and ACR in the direction of node B → node E is 2000 cps; therefore, for the route of node A → node B → node E, a minimum value of 1000 cps is selected as

the available cell rate.

In CTD 12a-2 is described an allowable cell transfer delay. In the case of the route i, CTD in the direction of node A → node B is 5 μs and CTD in the direction of node B → node E is 5 μs; therefore, for the route of node A → node B → node E, the sum of these values, that is, 10 μs, is set as CTD.

In CDV 12a-3 is described an allowable cell delay variation. In the case of the route i, CDV in the direction of node A → node B is 2 μs and CDV in the direction of node B → node E is 2 μs; therefore, for the route of node A → node B → node E, the sum of these values, that is, 4 μs, is set as CDV. The individual items of the routes ii and iii are determined in like manner.

In response to a request for the routing information, the routing information managing means 11 sends the DTL table 12a (or the inter-node routing information shown in FIG. 9) to the interwork QoS guaranteeing means 14. The interwork QoS guaranteeing means 14 determines whether or not the routing information sent from the routing information managing means 11 and the QoS parameter setting information 13a requested by the QoS setting means 13 satisfy respective QoS guaranteeing conditions mentioned below.

The QoS guaranteeing conditions are set as follows: For the band, QoS is guaranteed if [ACR of the route \geq requested PCR], for the delay, QoS is guaranteed if

[CTD of the route \leq requested CTD], and for the fluctuation, QoS is guaranteed if [CDV of the route \leq requested CDV].

With regard to the QoS parameter setting information 13a, ACR of the route (= 1000 cps) \geq requested PCR (= 50 cps), CTD of the route (= 10 μ s) \leq requested CTD (= 20 μ s), and the requested CDV = arbitrary. Accordingly, the route i can be recognized as a route meeting the requirements of the QoS parameter setting information 13a.

The route ii also satisfies the requirements of the QoS parameter setting information 13a, but the following description will be directed only to the route i, because the selection of one route from among a plurality of route options will be described later.

On judging that the route i fulfills the requirements of the QoS parameter setting information 13a, the interwork QoS guaranteeing means 14 notifies the call connection control means 15 of the QoS parameter setting information 13a, the routing list for the route i, and the ATM address of the terminating node E. The call connection control means 15 sets the items of information thus notified from the interwork QoS guaranteeing means 14 as the respective information elements of ATM Traffic Descriptor, Broadband Bearer Capability, DTL and Called Party Number, and makes a call connection request to the node E.

FIG. 11 shows the contents of settings of information elements of the call connection request message. Information elements 15b include ATM Traffic Descriptor, in

which "50 cps" is specified as PCR, Broadband Bearer Capability, in which CBR is specified as the service category, DTL, in which $A \rightarrow B \rightarrow E$ is specified as the routing list, and Called Party Number, in which the ATM address of the node E is specified as the terminating ATM address.

The call connection control means 15 thereafter receives a message responsive to the call connection request message from the node E, whereupon ATM connection (Data Direct VCC) is established along the route of node A \rightarrow node B \rightarrow node E.

For such ATM connection, optimum QoS suited to actual traffic of the LAN is selected. Consequently, after the switching of transmission from the frame transmission via the BUS to the transmission through ATM connection, frames can be transmitted from the LAN unit A1 to the LAN unit E1 over the ATM connection guaranteeing the optimum QoS.

Also, since QoS is determined beforehand in accordance with actual traffic and actual network and then the call connection control is performed, call can be connected efficiently without entailing useless lost calls.

A second embodiment will be now described. In the second embodiment, after a judgment is made that the QoS set first cannot be guaranteed, the interwork QoS guaranteeing means 14 adjusts the QoS so that the QoS can be guaranteed.

It is here assumed that the statistical information is the one shown in FIG. 5 as the TCP/IP

connection identifier #3 and, accordingly, that the QoS setting means 13 has set the QoS parameter setting information 13c shown in FIG. 8.

The QoS setting means 13 notifies the interwork
5 QoS guaranteeing means 14 of the QoS parameter setting information 13c having the contents shown in FIG. 8, that is, service category = VBR, PCR = 15000 cps, SCR = 6250 cps, MBS = 30000 cells, CTD = arbitrary, and CDV = 4 μ s or less, as well as the ATM address of the terminating node E.

10 On receiving the QoS parameter setting information 13c from the QoS setting means 13, the interwork QoS guaranteeing means 14 requests the routing information managing means 11 to provide routing information on routing up to the terminating node E.

15 The interwork QoS guaranteeing means 14 thereafter receives the routing information shown in FIG. 10 and judges that there is no route satisfying the requirements of the QoS parameter setting information 13c. Namely, the actual network currently available does not meet the requirements
20 of the QoS parameter setting information 13c.

In this case, however, the service category set in the QoS parameter setting information 13c is VBR. In view of the characteristics of VBR, the requested QoS can be almost perfectly guaranteed even if PCR cannot be guaranteed,
25 by increasing MBS instead.

Accordingly, with respect to the route ii which meets the requirement for CDV, the interwork QoS

guaranteeing means 14 decreases the requested PCR from "15000 cps" to "12000 cps" so that the requirements of the QoS parameter setting information 13c may be fulfilled.

MBS is instead increased to $30000 \times 15000/12000 =$
5 37500 cells. In this manner, QoS suited to actual traffic of the LAN is adjusted according to the status of resources of the actual network.

After adjusting the QoS parameter setting information 13c, the interwork QoS guaranteeing means 14
10 again requests the routing information managing means 11 to provide routing information, and receives the routing information therefrom. If, during this period of time, there has been no change in the routing information, then the adjusted QoS parameter setting information 13c (PCR =
15 12000 cps; SCR = 6250 cps; MBS = 37500 cells; CTD = arbitrary; CDV = 4 μ s or less) naturally satisfies the conditions of the route ii (ACR = 12000 cps; CTD = 20 μ s; CDV = 2 μ s), so that the QoS can be guaranteed by means of the route ii.

20 The interwork QoS guaranteeing means 14 notifies the call connection control means 15 of the adjusted QoS parameter setting information 13c, the routing list for the route ii, and the ATM address of the terminating node E.

The call connection control means 15 sets the
25 items of information thus notified from the interwork QoS guaranteeing means 14 as the respective information elements of ATM Traffic Descriptor, Broadband Bearer Capability, DTL

and Called Party Number, and makes a call connection request to the node E.

FIG. 12 shows the contents of settings of information elements of the call connection request message.

5 Information elements 15c include ATM Traffic Descriptor, in which "50 cps" is specified as PCR, Broadband Bearer Capability, in which VBR is specified as the service category, DTL, in which A → C → E is specified as the routing list, and Called Party Number, in which the ATM
10 address of the node E is specified as the terminating ATM address.

The call connection control means 15 thereafter receives a message responsive to the call connection request message from the node E, whereupon ATM connection (Data
15 Direct VCC) is established along the route of node A → node C → node E.

The QoS information notifying means 18 will be now described. After ATM connection is established, the QoS information notifying means 18 notifies the user of the QoS
20 information via the maintenance terminal unit 20. For example, in the case where the QoS requested first cannot be guaranteed and the adjusted QoS can instead be guaranteed, as in the second embodiment, the QoS information notifying means 18 transmits such items of information to the
25 maintenance terminal unit 20.

FIG. 13 illustrates the QoS information. The illustrated information is QoS information 18a derived in

the case of the second embodiment.

Specifically, the QoS which was requested first but could not be guaranteed is described as follows: service category = VBR, PCR = 15000 cps, SCR = 6250 cps, MBS = 30000
5 cells, CTD = arbitrary, and CDV = 4 μ s or less.

The reason for the failure to guarantee the QoS is described as follows: band deficiency (between the nodes A and B and between the nodes B and E) of the route i, band deficiency (between the nodes C and E) of the route ii, and
10 CDV of the route iii.

The QoS adjusted according to the actual network is described as follows: service category = VBR, PCR = 12000 cps, SCR = 6250 cps, MBS = 37500 cells, CTD = arbitrary, and
CDV = 4 μ s or less.

15 In this manner, the QoS information notifying means 18 notifies the user of the QoS information via the maintenance terminal unit 20, whereby the user can be readily informed of the current network status.

The route selecting means 19 will be now described.
20 FIG. 14 is a sequence diagram illustrating a route selection procedure. It is here assumed that the statistical information is the one shown in FIG. 5 as the TCP/IP connection identifier #1 and, accordingly, that the QoS setting means 13 has set the QoS parameter setting
25 information 13a shown in FIG. 8.

[S30] The QoS setting means 13 notifies the interwork QoS guaranteeing means 14 of the QoS parameter

setting information 13a having the contents shown in FIG. 8, that is, service category = CBR, PCR = 50 cps, CTD = 20 μ s, and CDV = arbitrary, as well as the ATM address of the terminating node E.

5 [S31] On receiving the QoS parameter setting information 13a from the QoS setting means 13, the interwork QoS guaranteeing means 14 requests the routing information managing means 11 to provide routing information on routing up to the terminating node E.

10 [S32] The interwork QoS guaranteeing means 14 receives the routing information shown in FIG. 10 from the routing information managing means 11, and recognizes that the routes i and ii fulfill the requirements of the QoS parameter setting information 13a.

15 [S33] The interwork QoS guaranteeing means 14 supplies the route selecting means 19 with route option information including the QoS parameter setting information 13a and the routing information about the routes i and ii.

20 [S34] The route selecting means 19 transmits the route option information to the maintenance terminal unit 20.

 [S35] The user specifies, for example, delay as a preferential QoS, and transmits the specified QoS to the route selecting means 19 through the maintenance terminal unit 20.

25 [S36] Since delay has been specified as the preferential QoS, the route selecting means 19 selects the route i having a smaller CTD value, and notifies the

interwork QoS guaranteeing means 14 that the route i has been selected.

[S37] The interwork QoS guaranteeing means 14 again requests the routing information managing means 11 to
5 provide routing information, in order to confirm whether or not there has been a change in the routing information.

[S38] If there has been no change in the routing information, the interwork QoS guaranteeing means 14 instructs the call connection control means 15 to connect
10 call via the route i.

Thus, in cases where there are a plurality of routes satisfying the requested QoS, the route selecting means 19 of the present invention selects a route in accordance with the QoS to which the user desires to give
15 priority.

This makes it possible to efficiently select a route that meets the user's expectations. Alternatively, QoS to be given priority may be set beforehand in the route selecting means 19 on the assumption that there exist a
20 plurality of routes meeting the requested QoS.

A network interconnection method according to the present invention will be now described. FIG. 15 illustrates a procedure of the network interconnection method.

25 [S40] The routing information of the ATM network is managed.

[S41] The statistical information on the traffic

of the LAN is managed.

[S42] QoS which the ATM network ought to guarantee is set based on the statistical information.

[S43] It is determined based on the routing
5 information whether or not the set QoS can be guaranteed.
If the set QoS cannot be guaranteed, the flow proceeds to
Step S44, and if the set QoS can be guaranteed, the flow
proceeds to Step S45.

[S44] The QoS is adjusted so that it can be
10 guaranteed, and the flow returns to Step S42.

[S45] Call is connected according to the QoS which
can be guaranteed.

As described above, according to the network
interconnection apparatus 10 and method of the present
15 invention, appropriate QoS to be guaranteed through ATM
connection is set with respect to a LAN-ATM interworking
communication node, based on the actual traffic of the LAN,
whereby ATM connection reflecting the status of resources of
the actual network can be established at a low rate of
20 occurrence of lost calls.

Even in the case where there is no route
satisfying the set QoS, the requested QoS is adjusted within
a range allowable with respect to the actual traffic of the
LAN, so that optimum QoS then available in the actual
25 network can be guaranteed.

Further, the user can be notified of the QoS which
can be guaranteed or of the QoS which cannot be guaranteed

as well as the reason for the failure to guarantee such QoS, and is also allowed to select a route as desired by specifying a preferential QoS parameter.

In the foregoing description, the QoS guarantee
5 determining means 14a is incorporated in the interwork QoS guaranteeing means 14, but it may alternatively be incorporated in the routing information managing means 11.

In this case, the interwork QoS guaranteeing means 14 receives from the routing information managing means 11
10 only the routing information which has been judged to fulfill the requested QoS.

As described above, the network interconnection apparatus according to the present invention is constructed such that QoS which can be guaranteed is determined based on
15 the routing information of the ATM network and the statistical information of the LAN, to connect call. Accordingly, optimum QoS suited to the status of actual traffic and actual network can be set, permitting efficient interwork control.

In the network interconnection method applied to
20 the apparatus of the present invention, QoS which can be guaranteed is determined based on the routing information of the ATM network and the statistical information of the LAN, to connect call. Consequently, optimum QoS suited to the
25 status of actual traffic and actual network can be set, making it possible to perform efficient interwork control.

The foregoing is considered as illustrative only

of the principles of the present invention. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and applications shown
5 and described, and accordingly, all suitable modifications and equivalents may be regarded as falling within the scope of the invention in the appended claims and their equivalents.

WHAT IS CLAIMED IS:

1. A network interconnection apparatus for interconnecting a LAN and an ATM network to perform
5 communications, comprising:

routing information managing means for managing routing information of the ATM network;

statistical information managing means for managing statistical information on traffic of the LAN;

10 QoS setting means for setting QoS which the ATM network ought to guarantee, based on the statistical information;

QoS guarantee determining means for determining based on the routing information whether or not the set QoS
15 can be guaranteed;

QoS adjusting means for adjusting the QoS so that the QoS can be guaranteed, if it is judged that the QoS cannot be guaranteed; and

call connection control means for performing call
20 connection according to the QoS which can be guaranteed.

2. The network interconnection apparatus according to claim 1, wherein said statistical information managing means manages, as the statistical information, a
25 traffic volume which is a sum of frame sizes or a total number of frames within a fixed time interval and which reflects traffic status of the LAN, and an average traffic

volume thereof.

3. The network interconnection apparatus according to claim 1, wherein said QoS setting means selects a constant transmission rate as service category if a maximum traffic volume is smaller than an augmented average traffic volume, and selects a variable transmission rate as the service category if the maximum traffic volume is greater than the augmented average traffic volume.

10 4. The network interconnection apparatus according to claim 1, wherein said QoS adjusting means adjusts a maximum burst size of QoS whose service category is variable transmission rate and whose maximum cell rate has been judged to be incapable of being guaranteed so that
15 the QoS can be guaranteed.

5. The network interconnection apparatus according to claim 1, further comprising QoS information notifying means for making notification of QoS information
20 to outside.

6. The network interconnection apparatus according to claim 1, further comprising route selecting means for selecting a route according to preferential QoS if
25 there exist a plurality of route options when the call connection is to be performed.

7. The network interconnection apparatus according to claim 1, which is connected to a maintenance terminal unit for performing maintenance and management.

5

8. A network interconnection method for interconnecting a LAN and an ATM network to perform communications, comprising:

managing routing information of the ATM network;
10 managing statistical information on traffic of the LAN;

setting QoS which the ATM network ought to guarantee, based on the statistical information;

determining based on the routing information
15 whether or not the set QoS can be guaranteed;

adjusting the QoS so that the QoS can be guaranteed, if it is judged that the QoS cannot be guaranteed; and

performing call connection according to the QoS
20 which can be guaranteed.

ABSTRACT OF THE DISCLOSURE

Network interconnection apparatus and method
5 capable of efficiently guaranteeing optimum QoS suited to
the status of actual traffic and network, whereby high-
performance network interconnection is achieved without
entailing lost calls. Routing information managing means
manages routing information of an ATM network, and
10 statistical information managing means manages statistical
information on the traffic of a LAN. QoS setting means sets
QoS which the ATM network ought to guarantee, based on the
statistical information, and QoS guarantee determining means
determines based on the routing information whether or not
15 the set QoS can be guaranteed. If it is judged that the QoS
cannot be guaranteed, QoS adjusting means adjusts the QoS so
that the QoS can be guaranteed. Call connection control
means connects call according to the QoS which can be
guaranteed.

20




FIG. 1




FIG. 2




FIG. 3




FIG. 4

11a STATISTICAL INFORMATION MANAGEMENT TABLE

TCP/IP CONNECTION IDENTIFIER	FIRST SAMPLING	SECOND SAMPLING	THIRD SAMPLING	FOURTH SAMPLING	FIFTH SAMPLING	AVERAGE TRAFFIC VOLUME
IDENTIFIER #1	1 9. 2 k	1 9. 2 k	1 9. 2 k	1 9. 2 k	1 9. 2 k	1 9. 2 k
IDENTIFIER #2	4. 8 M	4. 8 M	4. 8 M	4. 8 M	4. 8 M	4. 8 M
IDENTIFIER #3	2 4 0. 0 k	1 4 4. 0 k	5. 7 6 M	5. 7 6 M	9 6. 0 k	2. 4 M

(b p s)

FIG. 5

15a INFORMATION ELEMENT OF CALL CONNECTION REQUEST MESSAGE

INFORMATION ELEMENT	CONTENTS
ATM TRAFFIC DESCRIPTOR	PCR, SCR, MBS, ETC.
BROADBAND BEARER CAPABILITY	SERVICE CATEGORY, ETC.
DTL	ROUTING LIST, ETC.
CALLED PARTY NUMBER	TERMINATING ATM ADDRESS, ETC.
ETC.	-----

FIG. 6

SERVICE CATEGORY	CBR (CONSTANT BIT RATE)
	VBR (VARIABLE BIT RATE)
BAND	PCR (PEAK CELL RATE)
	SCR (SUSTAINABLE CELL RATE)
	MBS (MAXIMUM BURST SIZE)
DELAY	CTD (CELL TRANSFER DELAY)
FLUCTUATION	CDV (CELL DELAY VARIATION)

FIG. 7

QoS PARAMETER SETTING INFORMATION

TCP/IP CONNECTION IDENTIFIER	SERVICE CATEGORY	PCR	SCR	MBS	CTD	CDV
IDENTIFIER #1	CBR	50cps			$\leq 20 \mu s$	ARBITRARY
IDENTIFIER #2	CBR	12500cps			$\leq 20 \mu s$	ARBITRARY
IDENTIFIER #3	VBR	15000cps	6250cps	30000 CELLS	ARBITRARY	$\leq 4 \mu s$

13a

13c

FIG. 8




FIG. 9

12a DTL TABLE

ROUTE	ROUTING LIST	ACR	12a-1		12a-2		12a-3	
			CTD		CDV			
i	A → B → E	1 0 0 0 c p s	1 0 μ s		4 μ s			
i i	A → C → E	1 2 0 0 0 c p s	2 0 μ s		2 μ s			
i i i	A → D → E	1 5 0 0 0 c p s	3 0 μ s		5 μ s			

FIG. 10

15b INFORMATION ELEMENTS OF CALL CONNECTION REQUEST MESSAGE
(FIRST EMBODIMENT)

INFORMATION ELEMENT	CONTENTS
ATM TRAFFIC DESCRIPTOR	PCR=50 cps
BROADBAND BEARER CAPABILITY	SERVICE CATEGORY=CBR
DTL	ROUTING LIST=A → B → E
CALLED PARTY NUMBER	TERMINATING ATM ADDRESS=ATM ADDRESS OF NODE E

FIG. 11

15c CALL CONNECTION REQUEST PARAMETERS
(SECOND EMBODIMENT)

INFORMATION ELEMENT	CONTENTS
ATM TRAFFIC DESCRIPTOR	PCR=50 cps, SCR=6250 cps, MBS=37500 CELLS
BROADBAND BEARER CAPABILITY	SERVICE CATEGORY=CBR
DTL	ROUTING LIST=A → C → E
CALLED PARTY NUMBER	TERMINATING ATM ADDRESS=ATM ADDRESS OF NODE E

FIG. 12

18a QoS INFORMATION

QoS REQUESTED FIRST BUT FAILED TO BE GUARANTEED	SERVICE CATEGORY=VBR PCR=15000 cps SCR=6250 cps MBS=30000 CELLS CTD=ARBITRARY CDV=4 μ s OR LESS
REASON FOR FAILURE TO GUARANTEE	BAND DEFICIENCY OF ROUTE i & BAND DEFICIENCY OF ROUTE ii & CDV OF ROUTE iii
OPTIMUM QoS AFTER ADJUSTMENT (GUARANTEED QoS)	SERVICE CATEGORY=VBR PCR=12000 cps SCR=6250 cps MBS=37500 CELLS CTD=ARBITRARY CDV=4 μ s OF LESS

FIG. 13




FIG. 14

FIG. 15

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

NETWORK INTERCONNECTION APPARATUS

AND METHOD

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日 に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
（該当する場合） _____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されたとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づき国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

11-153276

(Number)
(番号)

Japan

(Country)
(国名)

(Number)
(番号)

(Country)
(国名)

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じていることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

01/06/1999

(Day/Month/Year Filed)
(出願年月日)

☐

(Day/Month/Year Filed)
(出願年月日)

☐

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)
(出願番号)

(Filing Date)
(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁護士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

書類送付先

Aaron B. KARAS, Reg. No. 18,923; Samson HELFGOTT, Reg. No. 23,072 and Leonard COOPER Reg. No. 27,625
Send Correspondence to:

HELGOTT & KARAS, P.C.
Empire State Building, 60th Floor
New York, New York 10118
United States of America

直接電話連絡先： (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Helfgott & Karas, P.C.
(212) 643-5000

唯一または第一発明者名	Full name of sole or first inventor
	Shinichi KURANARI
発明者の署名	Inventor's signature
日付	Date
	Kuranari Shinichi Dec. 3, 1999
住所	Residence
	Fukuoka-shi, Fukuoka, Japan
国籍	Citizenship
	Japanese
私書箱	Post Office Address
	c/o FUJITSU KYUSHU COMMUNICATION SYSTEMS LIMITED, 2-1, Momochihama
	2-chome, Sawara-ku, Fukuoka-shi, Fukuoka, 814-8588 Japan
第二共同発明者	Full name of second joint inventor, if any
	Fumiharu ETOH
第二共同発明者	Second inventor's signature
日付	Date
	Fumiharu Etoh Dec. 3, 1999
住所	Residence
	Fukuoka-shi, Fukuoka, Japan
国籍	Citizenship
	Japanese
私書箱	Post Office Address
	c/o FUJITSU KYUSHU COMMUNICATION SYSTEMS LIMITED, 2-1, Momochihama
	2-chome, Sawara-ku, Fukuoka-shi, Fukuoka, 814-8588 Japan

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)

第三共同発明者	Full name of third joint inventor, if any Tomoyuki FURUTONO		
第三共同発明者	日付	Third inventor's signature <i>Tomoyuki Furutono</i>	Date Dec. 3, 1999
住 所	Residence Fukuoka-shi, Fukuoka, Japan		
国 籍	Citizenship Japanese		
私書箱	Post Office Address c/o FUJITSU KYUSHU COMMUNICATION SYSTEMS LIMITED, 2-1, Momochihama 2-chome, Sawara-ku, Fukuoka-shi, Fukuoka, 814-8588, Japan		
第四共同発明者	Full name of fourth joint inventor, if any Hiroki HAMACHI		
第四共同発明者	日付	Fourth inventor's signature <i>Hiroki Hamachi</i>	Date Dec. 3, 1999
住 所	Residence Fukuoka-shi, Fukuoka, Japan		
国 籍	Citizenship Japanese		
私書箱	Post Office Address c/o FUJITSU KYUSHU COMMUNICATION SYSTEMS LIMITED, 2-1, Momochihama 2-chome, Sawara-ku, Fukuoka-shi, Fukuoka, 814-8588 Japan		

第五共同発明者	Full name of fifth joint inventor, if any		
第五共同発明者	日付	Fifth inventor's signature	Date
住 所	Residence		
国 籍	Citizenship		
私書箱	Post Office Address		

第六共同発明者	Full name of sixth joint inventor, if any		
第六共同発明者	日付	Sixth inventor's signature	Date
住 所	Residence		
国 籍	Citizenship		
私書箱	Post Office Address		

(第七以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for seventh and subsequent joint inventors.)

THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of: Shinichi KURANAI et al.

Filed: : Concurrently herewith

For : NETWORK INTERCONNECTION APPARATUS AND METHOD

Serial No.: Concurrently herewith

January 10, 2000

Assistant Commissioner of Patents
Washington, D.C. 20231

SUB-POWER OF ATTORNEY

S I R:

I, Samson Helfgott, Reg. No. 23,072 attorney of record herein, do hereby grant a sub-power of attorney to Linda S. Chan, Reg. No. 42,400, Jacqueline M. Steady, Reg. No., 44,354 and Harris A. Wolin, Reg. No. 39,432 to act and sign in my behalf in the above-referenced application. / /

Respectfully submitted,

Samson Helfgott
Reg.No 23,072

HELFGOTT & KARAS, P.C.
60th FLOOR
EMPIRE STATE BUILDING
NEW YORK, NY 10118
DOCKET NO.: FUJR 16.835
LHH:power

Filed Via Express Mail
Rec. No.: EL522353989US
On: January 10, 2000
By: L Gonzalez
Any fee due as a result of this paper, not covered
by an enclosed check may be charged on Deposit
Acct. No. 08-1634.